

# AIVECA AF HD

## PLOW LINE SUGARCANE

www.ikedamaq.com.br




AIVECA AF 6 PM/HD

### Project IKEDA makes the difference

- Line HD for extra heavy services developed to serve the sugarcane crop.
- Works at the desired depth, at any soil condition.
- Perfect incorporation of the haystack.
- Two types of mouldboard, one for each type of soil.




Flat  
(sandy soil)




Polyethylene  
(mixed clay soils)


### Shock Control




The mouldboard comes in contact with an obstacle.



The Shock Control is activated, disenga-ging the mouldboard.



The mouldboard rearms automatically with the simple lifting of the implement.



Return to the normal work.

| Modelo       | Mould-board  | Number of Mouldboards | Width Cut | Depth Cut  | Chassis Height | Safety        | Weight  | Power Minimum |
|--------------|--------------|-----------------------|-----------|------------|----------------|---------------|---------|---------------|
| AF - 4 LM/HD | Smooth       | 4                     | 180 cm    | 20 a 55 cm | 88 cm          | Shock Control | 1930 kg | 180 hp        |
| AF - 5 LM/HD | Smooth       | 5                     | 225 cm    | 20 a 55 cm | 88 cm          | Shock Control | 2280 kg | 225 hp        |
| AF - 6 LM/HD | Smooth       | 6                     | 270 cm    | 20 a 55 cm | 88 cm          | Shock Control | 2670 kg | 270 hp        |
| AF - 7 LM/HD | Smooth       | 7                     | 315 cm    | 20 a 55 cm | 88 cm          | Shock Control | 2970 kg | 315 hp        |
| AF - 8 LM/HD | Smooth       | 8                     | 360 cm    | 20 a 55 cm | 88 cm          | Shock Control | 3330 kg | 360 hp        |
| AF - 4 PM/HD | Polyethylene | 4                     | 180 cm    | 20 a 55 cm | 88 cm          | Shock Control | 1980 kg | 180 hp        |
| AF - 5 PM/HD | Polyethylene | 5                     | 225 cm    | 20 a 55 cm | 88 cm          | Shock Control | 2300 kg | 225 hp        |
| AF - 6 PM/HD | Polyethylene | 6                     | 270 cm    | 20 a 55 cm | 88 cm          | Shock Control | 2780 kg | 270 hp        |
| AF - 7 PM/HD | Polyethylene | 7                     | 315 cm    | 20 a 55 cm | 88 cm          | Shock Control | 3040 kg | 315 hp        |
| AF - 8 PM/HD | Polyethylene | 8                     | 360 cm    | 20 a 55 cm | 88 cm          | Shock Control | 3400 kg | 360 hp        |