

# MATABROTO ADB

## LINE SPROUT REMOVAL

www.ikedamaq.com.br

### MATABROTO EBT 220 M ADB with fertilizer bin and seed



#### Technical Characteristics

- Exclusive Rods in Tandem with helical curvature in high carbon steel, tempered, and quenched.
- High carbon steel blades with manganese alloy, tempered, and quenched.
- Rods in high carbon steel, tempered, and quenched.
- Fertilizer bins and seeds independent.



Dose valve



Straight Rod (EBR Model)

#### Shock Control



The rod finds an obstacle.



The Shock Control goes into action and disarms the rod.



The rod rearms automatically with the simple lifting of the implement.



Return to the normal work.

Model	Type	Blades	Width Work	Safety	Weight	Bin Capacity	Power Minimum
EBT 165 M ADB	Assembled	3	165 cm	Shock Control	915 kg	Fertilizer 710 kg / Seed 100 kg	95 hp 4x4
EBT 220 M ADB	Assembled	4	220 cm	Shock Control	950 kg	Fertilizer 710 kg / Seed 100 kg	105 hp 4x4
EBT 275 M ADB	Assembled	5	275 cm	Shock Control	1360 kg	Fertilizer 1080 kg / Seed 160 kg	150 hp 4x4
EBT 330 M ADB	Assembled	6	330 cm	Shock Control	1395 kg	Fertilizer 1080 kg / Seed 160 kg	180 hp 4x4
EBT 385 M ADB	Assembled	7	385 cm	Shock Control	1910 kg	Fertilizer 1453 kg / Seed 200 kg	230 hp 4x4
EBT 440 M ADB	Assembled	8	440 cm	Shock Control	1945 kg	Fertilizer 1453 kg / Seed 200 kg	270 hp 4x4
EBR 165 M ADB	Assembled	3	165 cm	Shock Control	915 kg	Fertilizer 710 kg / Seed 100 kg	95 hp 4x4
EBR 220 M ADB	Assembled	4	220 cm	Shock Control	950 kg	Fertilizer 710 kg / Seed 100 kg	105 hp 4x4
EBR 275 M ADB	Assembled	5	275 cm	Shock Control	1360 kg	Fertilizer 1080 kg / Seed 160 kg	150 hp 4x4
EBR 330 M ADB	Assembled	6	330 cm	Shock Control	1395 kg	Fertilizer 1080 kg / Seed 160 kg	180 hp 4x4
EBR 385 M ADB	Assembled	7	385 cm	Shock Control	1910 kg	Fertilizer 1453 kg / Seed 200 kg	230 hp 4x4
EBR 440 M ADB	Assembled	8	440 cm	Shock Control	1945 kg	Fertilizer 1453 kg / Seed 200 kg	270 hp 4x4